

	1	2	3	4	5	6	7																																																									
A																																																																
B																																																																
C																																																																
D																																																																
E	<p>①</p> <p><b>Technical Specification:</b></p> <ul style="list-style-type: none"> <li>Rated current: 5 A (RT)</li> <li>Nominal voltage: 50 VAC / 120 VDC</li> <li>AC Test voltage: 500 V</li> <li>Operating temperature: -50 to 100°C</li> <li>Mating cycles: min. 3</li> <li>Pitch: 2.54mm</li> <li>Contact resistance: &lt; 10mOhm</li> <li>Contact material: Bronze, gold flash plated</li> <li>Push-on force: ~4-5 N/contact</li> <li>Withdrawal force: ~2-3 N/contact</li> <li>Degree of protection: IP 00</li> <li>Insulation body: TPE</li> <li>Flammability category: UL 94 V-0</li> <li>Shore Hardness: 70A +-5</li> </ul>																																																															
F	<p>Packing : Bulk (1 250 pcs/bag)</p>																																																															
G	<p><b>ROHS compliant</b></p> <p>Unit:mm</p> <table border="1"> <thead> <tr> <th>Scale</th> <th>Free</th> <th></th> <th></th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>TOLERANCE</td> <td>±0.50</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.</td> <td>±0.30</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.X</td> <td>±0.20</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.XX</td> <td>±0.15</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.XXX</td> <td>±0.15</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td>±5°</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>							Scale	Free						TOLERANCE	±0.50						X.	±0.30						X.X	±0.20						X.XX	±0.15						X.XXX	±0.15						DIM	TOL						Angle	±5°						
Scale	Free																																																															
TOLERANCE	±0.50																																																															
X.	±0.30																																																															
X.X	±0.20																																																															
X.XX	±0.15																																																															
X.XXX	±0.15																																																															
DIM	TOL																																																															
Angle	±5°																																																															
H	<table border="1"> <thead> <tr> <th>Scale</th> <th>Free</th> <th></th> <th></th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>TOLERANCE</td> <td>±0.50</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.</td> <td>±0.30</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.X</td> <td>±0.20</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.XX</td> <td>±0.15</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.XXX</td> <td>±0.15</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td>±5°</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>							Scale	Free						TOLERANCE	±0.50						X.	±0.30						X.X	±0.20						X.XX	±0.15						X.XXX	±0.15						DIM	TOL						Angle	±5°						
Scale	Free																																																															
TOLERANCE	±0.50																																																															
X.	±0.30																																																															
X.X	±0.20																																																															
X.XX	±0.15																																																															
X.XXX	±0.15																																																															
DIM	TOL																																																															
Angle	±5°																																																															
	1	2	3	4	5	6	7																																																									
	<table border="1"> <thead> <tr> <th>Id.</th> <th>Modification</th> <th>Date</th> <th>Name</th> <th>Date</th> <th>Name</th> </tr> </thead> <tbody> <tr> <td>①</td> <td>updated of technical specification</td> <td>14.08.2013</td> <td>A. Plate</td> <td></td> <td></td> </tr> <tr> <td>②</td> <td>Drawn</td> <td>28.05.2013</td> <td>Winnie</td> <td></td> <td></td> </tr> </tbody> </table>							Id.	Modification	Date	Name	Date	Name	①	updated of technical specification	14.08.2013	A. Plate			②	Drawn	28.05.2013	Winnie																																									
Id.	Modification	Date	Name	Date	Name																																																											
①	updated of technical specification	14.08.2013	A. Plate																																																													
②	Drawn	28.05.2013	Winnie																																																													
	<p><b>ASSMANN</b> components</p>																																																															
	<p>Customer-No. ASSMANN WSW-No. ABT-B-300-040B</p>																																																															
	<p>Drawing-No. ASS 5718 CO rev01</p>																																																															
	<p>Replace SHEET 1</p>																																																															

**Technical Data:**

Terminal : CS191 R-H, Gold Flash

Insulator : TPE(Gray White, RAL 9002)

**Mechanical:**

Operating temperatures: 100°C

Hardness Shore: 70A±5

**Packing :** Bulk (1 250 pcs/bag)