



晶采光電科技股份有限公司  
AMPIRE CO., LTD.

## SPECIFICATIONS FOR LCD MODULE

<b>CUSTOMER</b>	
<b>CUSTOMER PART NO.</b>	
<b>AMPIRE PART NO.</b>	<b>AM-1024600K5TMQW-01H</b>
<b>APPROVED BY</b>	
<b>DATE</b>	

☐ Approved For Specifications

☐ Approved For Specifications & Sample

**AMPIRE CO., LTD.**

**4F., No.116, Sec. 1, Xintai 5th Rd., Xizhi Dist., New Taipei City 221,  
Taiwan (R.O.C.)**

**22181 新北市 汐止區 新台五路一段 116 號 4 樓(東方科學園區 A 棟)**

**TEL:886-2-26967269 , FAX:886-2-26967196 or 26967270**

<b>APPROVED BY</b>	<b>CHECKED BY</b>	<b>ORGANIZED BY</b>

## RECORD OF REVISION

Revision Date	Page	Contents	Editor
2015/06/11	--	New Release	Lawlite

## 1. Features

7 inch Amorphous-TFT-LCD (Thin Film Transistor Liquid Crystal Display) module. This module is composed of a 7" TFT-LCD panel, LED backlight, LED driver unit and power circuit unit.

- (1) Construction: 7" a-Si TFT active matrix, White LED Backlight and power & LED driver.
- (2) Resolution (pixel): 1024(R.G.B) X600
- (3) Number of the Colors : 16M colors ( R , G , B 6 bit digital each)
- (4) LCD type : Transmissive , normally White
- (5) Interface: LVDS interface 6bit (default), 8bit by jumper setting.
- (6) Viewing Direction: 6 O'clock (Gray Inversion)

## 2. PHYSICAL SPECIFICATIONS

Item	Specifications	unit
LCD size	7 inch (Diagonal)	
Resolution	1024 x 3(RGB) x 600	dot
Dot pitch	0.15(W) x 0.15(H)	mm
Active area	153.6(W) x 90.0(H)	mm
Module size	165. 5(W) x 104.44(H) x 7.41(D)	mm
Surface treatment	Hard Coating, Glare	
Color arrangement	RGB-stripe	
interface	LVDS	
Brightness	1000	cd/m <sup>2</sup>
Weight	TBD	g

### 3. ABSOLUTE MAX. RATINGS

Item	Symbol	Values		UNIT	Note
		Min.	Max.		
Power voltage	VCC	-0.3	4.2	V	
	VLED	-0.3	14		
Operation temperature	TOP	-20	70	°C	
Storage temperature	TST	-30	80	°C	

The following values are maximum operation conditions , If exceeded , it may cause faulty operation or damage

## 4. ELECTRICAL CHARACTERISTICS

### 4-1 Typical Operation Conditions

Item		Symbol	Values			Unit	Remark
			MIN	TYP	MAX		
Power Voltage		$V_{CC}$	3.0	3.3	3.6	V	Note 1,2
Power Consumption		$I_{CC}$	--	150	--	mA	Note 1,2 $V_{CC}=3.3V$
Logic Input Voltage	Input Voltage	$V_{IN}$	0	-	$V_{CC}$	V	
	Logic input high voltage	$V_{TH}$	$0.7V_{CC}$	-	$V_{CC}$	V	Note 3
	Logic input low voltage	$V_{TL}$	GND	-	$0.3V_{CC}$	V	Note 3

Note 1: Value for Power Board combined panel.

Note 2: VCC setting should match the signals output voltage (refer to Note 3) of customer's system board.

Note 3: LVDS.

## 4-2 LED Driving Conditions

Item	Symbol	Values			Unit	Note
		Min.	Typ.	Max.		
LED Driver Power Voltage	$V_{LED}$	9	12	14	V	
LED Driver Current Consumption	$I_{LED}$	--	730	--	mA	$V_{LED}=12V$ $ADJ=5V$ (duty 100%)
ADJ Input Voltage	$V_{ADJ-IH}$	1.2	--	$V_{LED}$	V	duty=100% Note(3)
	$V_{ADJ-IL}$	0	--	0.5	V	
LED voltage	$V_{AK}$	24.8	25.6	26.4	V	Note(1)
LED forward Current	$I_{AK}$	--	240	--	mA	$T_a=25^{\circ}C$
LED life time	--	--	50,000	--	Hr	Note(2)


Note (1) The constant current source is needed for white LED back-light driving.

When LCM is operated over 60 deg.C ambient temperature.

Note (2) Brightness to be decreased to 50% of the initial value.

Note (3)  $V_{LEDADJ}$  is PWM signal input. It is for brightness control.


There are 5 Groups LED shown as below ,  $V_{AK} = 25.6V$  ,  $I_{AK} = 240mA$ .




Brightness to be decreased to 50% of the initial value.

### 4-3 Power Sequence

#### a. Power on:



#### b. Power off:



## 5. Optical Specifications


Item	Symbol	Condition	Values			Unit	Note
			Min.	Typ.	Max.		
Viewing angle (CR $\geq$ 10)	$\theta$ L	$\Phi = 180^\circ$ (9 o'clock)	65	75	--	degree	Note1
	$\theta$ R	$\Phi = 0^\circ$ (3 o'clock)	65	75	--		
	$\theta$ T	$\Phi = 90^\circ$ (12 o'clock)	65	70	--		
	$\theta$ B	$\Phi = 270^\circ$ (6 o'clock)	65	75	--		
Response time	TON	Normal $\theta = \Phi = 0^\circ$	--	20	30	msec	Note3
	TOFF		--	20	30	msec	
Contrast ratio	CR		500	700	--	--	Note4
Color chromaticity	WX		0.249	0.299	0.349	--	Note5
	WY		0.273	0.323	0.373	--	Note6
Luminance	L		800	1000	--	cd/m <sup>2</sup>	Note6

Test Conditions:

1. Vled = 12V, IL = 180mA (Backlight current), the ambient temperature is 25°C.
2. The test systems refer to Note 2.


Note 1 : Definition of viewing angle range






Note 2 : Definition of optical measurement system.

The optical characteristics should be measured in dark room. After 30 minutes operation, the optical properties are measured at the center point of the LCD screen. (Response time is measured by Photo detector TOPCON BM-7, other items are measured by BM-5A/Field of view :  $1^\circ$  / Height : 500mm.)



Note 3 : Definition of Response time

The response time is defined as the LCD optical switching time interval between “White” state and “Black” state. Rise time ( $T_{ON}$ ) is the time between photo detector output intensity changed from 90% to 10%. And fall time ( $T_{OFF}$ ) is the time between photo detector output intensity changed from 10% to 90%.



Note 4 : Definition of contrast ratio

$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when LCD on the "White" state}}{\text{Luminance measured when LCD on the "Black" state}}$$

Note 5 : Definition of color chromaticity (CIE1931)

Color coordinated measured at center point of LCD.

Note 6 : All input terminals LCD panel must be ground when measuring the center area of the panel.

## 6. INTERFACE

### CN2

Pin No.	Symbol	I/O	Description	Note
1	VDD	P	Power Voltage for Logic: 3.3V	
2	VDD	P	Power Voltage for Logic: 3.3V	
3	U/D	I	Vertical Reverse Scan Control	
4	L/R	I	Horizontal Reverse Scan Control.	
5	IN0-	I	- LVDS differential data input	
6	IN0+	I	+ LVDS differential data input	
7	GND	P	Ground	
8	IN1-	I	- LVDS differential data input	
9	IN1+	I	+ LVDS differential data input	
10	GND	P	Ground	
11	IN2-	I	- LVDS differential data input	
12	IN2+	I	+ LVDS differential data input	
13	GND	P	Ground	
14	CLK-	I	- LVDS differential data input	
15	CLK+	I	+ LVDS differential data input	
16	GND	P	Ground	
17	IN3-	I	- LVDS differential data input	
18	IN3+	I	+ LVDS differential data input	
19	VLED	P	Power supply for backlight:12V	
20	ADJ	I	LED PWM signal	

I : input, O : output, P : power

**CN3**

Pin No.	Symbol	I/O	Description	Note
1	VLED	P	Power supply for backlight:12V	
2	GND	P	Ground	
3	NC		No Connect	
4	ADJ	P	LED PWM signal	
5	NA		No Connect	

NOTE :



(1) ADJ is PWM signal input. It is for brightness control.

ITEM	SYMBOL	MIN	TYP	MAX	UNIT
ADJ signal frequency	f <sub>PWM</sub>	10	--	100	KHz
ADJ signal logic level High	VIH	1.2	--	VLED	V
ADJ signal logic level Low	VIL	0	--	0.5	V

## 7. TIMING CHARACTERISTICS


### 7-1 AC Electrical Characteristics

Parameter	Symbol	Values			Unit	Remark
		MIN	TYP	MAX		
Clock frequency	$R_{xFCLK}$	40.8	51.2	71		
Input data skew margin	$T_{RSKM}$	500	--	--		
Clock high time	$T_{LVCH}$	--	$4/(7 * R_{xFCLK})$	--		
Clock low time	$T_{LVCL}$	--	$3/(7 * R_{xFCLK})$	--		



## 7-2 DC Electrical Characteristics

Item	Symbol	Values			Unit	Note
		Min.	Typ.	Max.		
Differential input high Threshold voltage	$R_{xVTH}$	-	-	+0.1	V	$R_{xVCM}=1.2V$
Differential input low Threshold voltage	$R_{xVTH}$	-0.1	-	-	V	
Input voltage range (singled-end)	$R_{xVIN}$	0	-	2.4	V	
Differential input common mode voltage	$R_{xVCM}$	$ V_{ID} /2$	-	$2.4- V_{ID} /2$	V	
Differential voltage	$ V_{ID} $	0.2	-	0.6	V	
Differential input leakage current	$RV_{xliz}$	-10	-	+10	uA	




### 7-3 Timing


Item	Symbol	Values			Unit	Note
		Min.	Typ.	Max.		
Clock Frequency	fclk	40.8	51.2	67.2	MHz	Frame rate =60Hz
Horizontal display area	thd	1024			DCLK	
HS period time	th	1114	1344	1400	DCLK	
HS Blanking	thb	90	320	376	DCLK	
Vertical display area	tvd	600			H	
VS period time	tv	610	635	800	H	
VS Blanking	thb	10	35	200	H	

**Default setting: 6bits LVDS input. (JP2 on PCBA)**

**6bit LVDS input**



**8bit LVDS input**





## 8. RELIABILITY TEST CONDITIONS

(Note 3)

Item	Test Conditions	Note
High Temperature Storage	Ta = 80°C 240 hrs	Note 1,4
Low Temperature Storage	Ta = -30°C 240 hrs	Note 1,4
High Temperature Operation	Ts = 70°C 240 hrs	Note 2,4
Low Temperature Operation	Ta = -20°C 240 hrs	Note1,4
Operate at High Temperature and Humidity	+60°C, 90%RH 240 hrs	
Thermal Shock	-30°C /30 min ~ +80°C /30 min for a total 100 cycles, Start with cold temperature and end with high temperature	

Note 1 : Ta is the ambient temperature of samples.

Note 2 : Ts is the temperature of panel's surface.

Note 3 : In the standard condition, there shall be no practical problem that may affect the display function. After the reliability test, the product only guarantees operation, but don't guarantee all of the cosmetic specification.

Note 4 : Before cosmetic and function test, the product must have enough recovery time, at least 2 hours at room temperature.

## **9. General Precautions**

### **9-1 Safety**

Liquid crystal is poisonous. Do not put it your mouth. If liquid crystal touches your skin or clothes, wash it off immediately by using soap and water.

### **9-2 Handling**

1. The LCD panel is plate glass. Do not subject the panel to mechanical shock or to excessive force on its surface.
2. The polarizer attached to the display is easily damaged. Please handle it carefully to avoid scratch or other damages.
3. To avoid contamination on the display surface, do not touch the module surface with bare hands.
4. Keep a space so that the LCD panels do not touch other components.
5. Put cover board such as acrylic board on the surface of LCD panel to protect panel from damages.
6. Transparent electrodes may be disconnected if you use the LCD panel under environmental conditions where the condensation of dew occurs.
7. Do not leave module in direct sunlight to avoid malfunction of the ICs.

### **9-3 Static Electricity**

1. Be sure to ground module before turning on power or operation module.
2. Do not apply voltage which exceeds the absolute maximum rating value.

### **9-4 Storage**

1. Store the module in a dark room where must keep at  $+25\pm 10^{\circ}\text{C}$  and 65%RH or less.
2. Do not store the module in surroundings containing organic solvent or corrosive gas.
3. Store the module in an anti-electrostatic container or bag.

### **9-5 Cleaning**

1. Do not wipe the polarizer with dry cloth. It might cause scratch.
2. Only use a soft cloth with IPA to wipe the polarizer, other chemicals might permanent damage to the polarizer.

### 9-5 Others

1. AMIPRE will provide one year warrantee for all products and three months warrantee for all repairing products.
2. Do not apply fixed pattern data signal to the LCD module at product using.  
The residual image may exist if the same display pattern is shown for hours. This residual image, however, disappears when another display pattern is shown or the drive is interrupted and left for a while. But this is not a problem on reliability.

Operation with test pattern sustained for 4 hrs, then change to gray pattern immediately. After 5 mins, the mura must be disappeared completely .




Image Sticking -pattern



Mid-Gray pattern



